



**SPECIFICATIONS:** **INSTALLATION:**

**Motor:** Brushless 3450 RPM, 1/8 hp motor, capacitor initiated, thermally protected against overheating.  
**Fan:** Dynamically balanced to eliminate vibration/noise.  
**Heating Element:** 2300 watt nichrome wire, mounted on state of the art convective heating injection system mounted to blower housing, protected by integral safety circuit breaker.  
**Timer:** Fully enclosed electronic timer that can be adjusted to requirements at any time after installation.  
**Button Assembly:** Heavy duty push button assembly has a stop action to further protect timer mechanism.  
**Cover:** Heavy die cast aluminum with baked white enamel finish and ribbed for added strength. Secured to base with two theft resistant fasteners.  
**Nozzle:** Chrome plated that can be fixed or two position.  
**Base:** One piece #14 ga steel with 3/4" returns to wall for maximum strength and rigidity.

Unit	Volts	Amps	Cycles
U1525-120	110-120	18	60
U1525-230	208-230	10	60

**Overall Size:** 12 7/8"W x 8 3/4"H x 6 5/8"D  
 327mm x 222mm x 168mm  
**Optional Colors:** -20: Beige, -21: Red, -22: Black, -23: Almond, -24 Grey, -CHR: Chrome.

Coordinate installation with contractor, architect and licensed electrician. Transfer mounting points to wall surface with supplied template. Check all code requirements for proper mounting heights. Secure base to surface with proper fasteners per application. Properly connect power supply to dryer and test operation and adjust timer mechanism. Secure dryer to base and test dryer again after cover is secured.  
*Recommend 1 dryer per basin.*

**JETAIR dryers have a full five (5) year warranty to original purchaser against defective materials and workmanship. Unit must be installed by a licensed electrician.**

Mounting	Hands	Hair
Men	46" (1168mm)	73" (1854mm)
Women	44" (1118mm)	68" (1727mm)
Physically Impaired	38" (965mm)	46" (1168mm)
Children 6-10	34" (864mm)	43" (1092mm)
Children 11-14	42" (1067mm)	56" (1422mm)

*\*Above are recommended mounting heights from lower mounting point above the finished floor.*

**APPLICATION:**

To provide a surface mounted dryer that is UL approved, push button operational and meets ADA code when mounted properly.



Form: U1525/2000